

## S-3822A/S

### 2-ch Simultaneous Battery Charger & Adaptor



S-3822S  
for V-Mount

S-3822A  
for Gold Mount

#### Features

- ◆ Portable battery charger
- ◆ 2-ch simultaneous charging
- ◆ 3A charging current per channel
- ◆ LED charging indicators
- ◆ Support AC to 4-pin XLR output

#### Specifications:

Input	100~240VA, 50/60Hz
Power	136W(Max)
Charging Output	DC 16.8V, 3A(Max)×2
Adapting Output	DC 15V, 6A(Max)
Operating Temperature	-20°C ~ +50°C
Working Humidity	10% ~ 90%
Dimensions (without battery mount)	228mm×140mm×60mm
Dimensions (with battery mount)	228mm×140mm×86mm(S-3822A) 228mm×140mm×102mm(S-3822S)
Weight	Appx 1.0kg



Can charge 2x **V-mount / Gold mount** batteries simultaneously. The charging output is DC **16.8V, 3Ax2**



LED indicates the charging status for each channel:  
**Red:** on charging, <100%  
**Green:** charging finished.



AC-DC adapting output via 4-pin XLR female connector. Offer DC **15V, 6A, 90W** output. (will not output when battery is charging)



Facebook Page



Instagram